

SOUNDBOKS 4 — TECH SPECS

SOUND

- 3 × 72W RMS Infineon MERUS Audio eximo® class D amplifiers
- Next generation adaptive DSP with proprietary Bass Enhancer
- Effective frequency range: 40 Hz - 20 kHz
- 126 dB max volume
- Pulse Reflex port
- 2 × 10" 96 dB / 1W / 1m woofers and 1 × 1" 104 dB / 1W / 1m compression driver tweeter

BUILD

- Water resistant
- Poplar cabinet
- Snap-on removable powder coated steel grill
- Powder-coated aluminum frame and steel handles
- Silicone ball corners
- 25.6×17×13 inches / 66×43×32 cm (H × W × D)
- 35.5 pounds (16.1 kg)
- IP65 rated electronics coating

USER INTERFACE

- Power on/off button
- Volume control knob with LED indicators
- Bluetooth LED indicator
- TeamUP button with LED indicators for Solo/Host/Join mode

BATTERY

- 40 hours at mid-volume
- 6 hours at full volume (default sound profile)
- 3.5 hours full recharge time
- 12.8 V, 7.8 Ah Lithium Iron Phosphate (LiFePO4)
- 99.84 Wh or 7.8 Ah capacity
- Heavy-duty DC-connector
- 5-step LED battery indicator
- 5F to 131F temperature range
- Short circuit protection
- Overheat protection

CONNECTIVITY

- Bluetooth 5.0
- TeamUP connection (SKAA) for up to 5 SKAA-enabled speakers
- Pro Panel:
 - 2 × Combo (XLR, 1/4") balanced inputs
 - 1 × 3.5mm stereo input
 - 1 × 3.5mm stereo output
 - Bond Button for advanced JOIN settings

APP

- Upgradeable firmware
- Custom sound profiles with customizable EQ
- Pro Panel configuration:
 - Input type selection: Line-in, mic, instruments
 - Control for EQ and Input Gain
- Bluetooth PIN code

Description	SOUNDBOKS 4 - Black	SOUNDBOKS 4 - Metallic Grey
SKU	11-SB4_B_US	11-SB4_T_US
EAN	5714295004319	5714295004340
GTIN	5714295004326	5714295004357
Package Dimension	741X395X530 mm	741X395X530 mm
Net weight	16,1 kgs	16,1 kgs
Grossweight	21,5 kgs	21,5 kgs
HS code	85.18.22.00.90	85.18.22.00.90
UN number	UN3481 - Contained in equipment	UN3481 - Contained in equipment