



Technical Specifications





	Rianzie Filenginei	
Details	B13/150	B16/250
Operating pressure	30 - 150 bar	20 - 250 bar
Max. admissible overpressure	170 bar	250 bar
Water output	13 l/min	16 l/min
Nozzle size (flat jet)	2505	25045
Dirtkiller lance	Additional	Additional
Max. inlet water temperature	60°C	60°C
Hose drum	Yes - 20m	Yes - 20m
Chemical injector	Additional	Additional
Motor	Honda GX160 with 2:1 Reduction Gearbox	Honda GX390 with 2:1 Reduction Gearbox

Motor power

Powerful, compact and conveinient

5.5 HP

www.kranzle.co.za

Features

- Stainless steel frame fitted with 500l water tank
- Service-friendly Honda engine
- 2:1 Reduction gearbox
- 20m Steel double braided highpressure hose and hose reel
- Sludge sucker with hose for easy refilling
- Fits all single and double cab bakkies

Ideal for

- Fighting fires or cleaning areas with no power or water source
- Removes paint, posters and graffiti from buildings
- Pump sludge (manholes, septic tanks etc.) or water at 16 000l/hour
- Clean roods, factory floors, machinery, motor vehicles and engines
- Disinfect large areas (chicken runs etc.) or dip spray animals
- Effective sandblasting, i.e. removal of road markings
- Blocked drains

Kränzle Firefighter

13 HP