



Features

- Water tank with low level cut-out
- Current overload protection
- 7.5m power lead with cable reel
- Shock absorbing buffers
- Parking brake
- Brass pump head
- Ceramic-coated stainless steel pump pistons
- Continuously adjustable pressure control
- Dry-run safety
- Total-Stop system with delayed motor cut-out
- Trigger gun with safety catch
- Stainless steel lance with flat jet nozzle lance
- Includes Turbokiller rotating nozzle lance
- 10m Steel braided high-pressure hose

Technical Specifications Kränzle Quadro 800 TS / 1000 TS / 1200 TS



Details	800 TS	1000 TS	1200 TS
Operating pressure	30 - 250 bar	30 - 220 bar	30 - 180 bar
Max. admissible over-pressure	270 bar	250 bar	200 bar
Water output	13.3 l/min	16.1 l/min	19 l/min
Nozzle size (flat jet)	2504	2505	2507
Turbokiller lance	Included	Included	Included
Max. inlet water temperature	60°C	60°C	60°C
Hose drum	Additional	Additional	Additional
Chemical injector	Yes	Yes	Yes
Connected load - 50Hz	400V, 12 A	400V, 12 A	400V, 12 A
Motor speed	1 400 r.p.m	1 400 r.p.m	1 400 r.p.m
Motor rating	5.5kW	5.5kW	5.5kW

Specialist equipment for professional application