

- ✓ With fluid recovery system
- ✓ Integrate high quality swivel
- ✓ Ready to use

Mosmatic Allrounder with recovery is ideal for smaller and hard to reach areas both indoors and out. Small compact and lightweight design is ideal for jobs large or small. Using your vac system, water can be recovered, reused or discharged.



**TECHNICAL DATA**

**Pressure** 275 bar  
**Temperature** 120°C  
**Inlet** G3/8" F



**FL-AER 410**



**FL-AER 300**

**FL-AER 200**


**FL-AEB 200**

**FEATURES**

**Recovery System**

Environmental protection is more important than ever. These recovery units have a double wall housing to optimize vacuum power.

Residual water and debris can be recovered, recycled and reused.



**Rotor Arms**

Can withstand up to 275 bar, are precision welded and balanced.

- 2w2** (2 Arms / 2 Nozzles) Part No. 82.621 (ø150 mm)
- 2w2** (2 Arms / 2 Nozzles) Part No. 82.623 (ø250 mm)
- 2w2** (2 Arms / 2 Nozzles) Part No. 82.625 (ø350 mm)



**Proven innovation**

Developed by Mosmatic and in service for years, the toggle swivel has proven itself. The toggle joint feature allows effortless cleaning of walls and angled surfaces. The movement of the joint is adjustable for fatigue free cleaning.



**KDYF Toggle Swivel**

Part No. 58.908

**Quality Swivel**

High rpm stainless steel swivel, features reinforced self lubricated stainless steel ball bearings for improved performance. The dual spring based carbide seal system, guarantees long lasting operation under tough conditions.



**DYF Swivel**

Part No. 58.000 (ø200 mm) Part No. 58.250 (ø410 mm)

**Stainless Steel Caster**

Heavy duty ø60 mm casters with custom mounting brackets ensure easy maneuvering even in confined spaces.



**Stainless Steel Caster**

Part No. 80.943

**Caster for ø200 mm**

Part No. 80.922

Name	Part No.	ø	Weight	Swivel	Rotor Arm	Nozzles	HP-Gun	Wheels
FL-AEB 200	78.230	200	2.8 kg	1x DYF	2x 1/8" NPTF	2x 18.1503	1x	--
FL-AER 200	78.240	200	4.2 kg	1x KDYF	2x 1/8" NPTF	2x 18.1503	1x	3x ø42
FL-AER 300	78.242	300	5.6 kg	1x KDYF	2x 1/8" NPTF	2x 18.1503	1x	3x ø60
FL-AER 410	78.249	410	9.0 kg	1x DYF	2x 1/8" NPTF	2x 18.1503	1x	3x ø60