

- ✓ Also model up to 500 bar available
- ✓ Maintenance free
- ✓ Quality stainless steel swivel
- ✓ Ready to use

The surface cleaner for cold and hot water application reaches peak performance without any maintenance. Our most popular flat surface cleaner, ideal for cleaning parking lots, gas stations, school yards, entrance halls etc.



TECHNICAL DATA

Pressure	275 / 500 bar
Temperature	120°C
Inlet	G3/8" F G1/4" M



FL-CR 750



FL-CR 520

FL-CG 520

FEATURES

Rotor Arms

Can withstand up to 500 bar, are precision welded and balanced.

2cw2 (2 Arms / 2 Nozzles)

Part No. 82.942 (ø470 mm)

3cw3 (3 Arms / 3 Nozzles)

Part No. 82.943 (ø700 mm)

2cp2 (2 Arms / 2 Nozzles)

Part No. 82.946 (ø470 mm), 1/8", 500 bar

Optional: Part No. 82.941 (ø470 mm), 1/4", 500 bar

Optional: Part No. 82.9069 (ø450 mm), 1/8", 500 bar

3cp3 (3 Arms / 3 Nozzles)

Part No. 82.947 (ø700 mm), 1/8", 500 bar



Stainless Steel Caster

Heavy duty ø60 mm casters with custom mounting brackets ensure easy maneuvering even in confined spaces.



Stainless Steel Caster

Part No. 80.912

Quality Swivel

High rpm stainless steel swivel features reinforced self lubricated stainless steel ball bearings for improved performance. The dual spring based carbide seal system, guarantees long lasting operation under tough conditions.



DYCI Swivel

Part No. 55.253

DYDI Swivel (500 bar)

Part No. 55.263

Name	Part No.	ø	Weight	Swivel	Rotor Arm	HD- Nozzles	HP- Gun	Stainless Steel Caster
FL-CG 520	80.750	520	10.3 kg	1x DYCI	2x 1/8" NPTF	2x 18.1503	1x	--
FL-CR 520	80.751	520	12.0 kg	1x DYCI	2x 1/8" NPTF	2x 18.1503	1x	4x ø60
FL-RY 520*	80.158	520	11.5 kg	1x DYDI	2x 1/8" NPTF	--	--	4x ø60
FL-RY 750*	80.358	750	13.5 kg	1x DYDI	3x 1/8" NPTF	--	--	4x ø60
FL-CR 750	80.752	750	15.5 kg	1x DYCI	3x 1/8" NPTF	3x 18.1503	1x	4x ø60

* Pressure: 500 bar / Inlet G1/4" M