- ✓ Effective and efficient cleaning
- ✓ With fluid recovery system
- ✓ Gum remover bracket







FL-AHB-KAU 750



FL-AHB-KAU 520



Mosmatic takes the edge off work with the "All in one" cleaning tool. Remove chewing gum from public areas such as sidewalks, train stations, parks and school facilities. The gum will be cut and lifted ready to be recovered. No chemicals needed.



FEATURES

Chewing Gum remover

This special nozzle, uses it's own trigger gun to activate on chewing gum or persistent stains. The high pressure jets impact at a 45° angle to cut and lift the gum. Available sizes: #3 (29.102), #4 (29.103), #5 (29.119)




Gum remover nozzle sold separately.

Recovery System

Environmental protection is more important than ever, leading to the need to recycle waste water. The dual housing and vacuum port allow this function.

Residual water and debris can be recovered, recycled and reused.



Adjustable Height

Stainless steel frame for added stability. Optimize your cleaning results with the height adjustable housing.

Stainless Steel Caster (Premium Quality)

Four 100 mm stainless steel casters with custom mounting brackets, ensure easy maneuvering even in confined spaces. Part No. 80.956



Rotor Arms

Can withstand up to 500 bar, and are precision welded and balanced.

2cp2 (2 Arms / 2 Nozzles) 3cp3 (3 Arms / 3 Nozzles) Part No. 82.946 (ø470 mm) Part No. 82.947 (ø700 mm) Optional: Part No. 82.9069 (ø450 mm), 1/8*



Quality Swivel

High rpm stainless steel swivel, features reinforced self lubricated stainless steel ball bearings for improved performance. The dual spring based carbide seal system, guarantees long lasting operation under tough conditions.



DYCI Swivel

Part No. 55.253

Name	Part No.	Ø	Weight	Swivel	Rotor Arm	HP- Nozzles	HP- Gun	Stainless Steel Caster
FL-AHB-KAU 520	80.766	520	20.0 kg	1x DYCI	2x 1/8" NPTF	2x 18.1503	2x	4x ø100
FL-AHK-KAU 520*	80.767	520	20.0 kg	1x DYCI	2x 1/8* NPTF	2x 18.1503	2x	4x ø100
FL-AHB-KAU 750	80.768	750	26.5 kg	1x DYCI	3x 1/8" NPTF	3x 18.1503	2x	4x ø100

^{*} with plastic rim guard, no brush ring