



2,45^{kW}

STEAM CLEANER
00

STEAM CLEANER						
Model		Det	Water	24/7	Base	
Boiler		Stainless-steel AISI 304 with interchangeable heating element				
Body		Stainless-steel AISI 304 BA				
Power supply	V - Hz	1~ 230 - 50/60				
Boiler output	kW/h	2,4				
Maximum output	kW/h	2,45				
Boiler volume	1		1,5		3	
Operating pressure	bar		8		6	
Water tank	1		3		-	
Detergent tank	1	1	-	-	-	
Steam production	g/min		6	4		
	Kg/h		3,	,8		
Steam temperature	° C		174		165	
Detergent temperature	° C	90 - 160	-	-	-	
VARIOUS						
Weight	Kg		1	6		
Cable	m		5	5		
Dimensions (generator)	cm	H.32,6 x L.27,8 x W. 43,6				
Dimensions (pallet)	cm	53 x 40 x 52				
Pallet/unit	pz	24				





Technical features



pressure 8 bar



Operating pressure 6 bar



Water tank



Detergent tank



refilling



injection



water injection





maintenance signal

Steam cleaner designed for professional use with stainless-steel body and boiler:

- · Able to deliver dry saturated steam 174° or 165°C
- · Available with detergent injection or overheated water injection
- · The ergonomic structure, the fully electric operation and the compact size allows its to usage in any environment.
- · All steam cleaner functions can be managed on the electronic control panel.
- Equipped with cable holder and anti-scratch 360° swivel front wheels.





Features



Optional

Trolley ARENA PLUS

Control panel

Electric plug SHUKO 5m

Steam outlet

Water tank - 3 l

only on mod. DET - WATER - 24/7







Cable holder



System ON



CONTROL PANEL

- · Display to visualize temperature and pressure levels, working hours and boiler cleaning signal
- **Buttons and indicators for the** complete control of the parameters of the steam cleaner



Optional accessories

Evo 304 can be used with the following accessories:







STEAM MOP 6 bar Steam accessories






APPLICATIONS





HO.RE.CA







HOUSEHOLD











