



#### STEAM CLEANER

Boiler		Stainless-steel AISI 304 with interchangeable heating element
Body		ABS VO - Varnished steel P04
Power supply	V - Hz	1~ 230 - 50/60
Boiler output	kW/h	2,4
Maximum output	kW/h	2,45
Boiler volume	1	1,5
Operating pressure	bar	6 8
Water tank	1	3
Steam production	g/min	64
	Kg/h	3,8
Steam temperature	° C	165 174

## VARIOUS

Weight	Kg	14
Cable	m	5
Dimensions (generator)	cm	H.33 x L.32 x W. 41
Dimensions (pallet)	cm	53 x 40 x 52
Pallet/unit	pz	24



### Technical features















Operating pressure 8 bar

pressure 6bar

Automatic water refilling

Overheated water injection

Control panel

maintenance signal

#### Steam cleaner with ABS and varnished-steel body and stainless-steel boiler, designed for professional use:

- · Able to deliver dry saturated steam at 165°C or 174°C.
- Equipped with an overheated water injection system (available only for the 8-bar model).
- · The ergonomic structure, the fully electric operation and the compact size allows its to usage in any
- · All steam cleaner functions can be managed on the electronic control panel.
- Equipped with cable holder and anti-scratch 360° swivel front wheels.







## **CONTROL PANEL**

- · Display to visualize temperature and pressure levels, working hours and boiler cleaning signal
- **Buttons and indicators for the** complete control of the parameters of the steam cleaner



# **Optional accessories**

Gal can be used with the following accessories:







## **STEAM MOP 6 bar Steam accessories**






## **APPLICATIONS**





HO.RE.CA







HOUSEHOLD

HEALTH CARE









